

## TABLES

| NWF R2MF Final Calibration Metrics |                        |                          |                        | Task 1 Goals              |                         |
|------------------------------------|------------------------|--------------------------|------------------------|---------------------------|-------------------------|
| Calibration Target Type            | Calibration Metric     | Domain-Wide Metric Value | Subregion Metric Value | Domain-Wide Metric Target | Subregion Metric Target |
| Post-dev Groundwater Heads         | Mean Error             | 0.40                     | -0.08                  | +/- 5 ft                  | +/- 2 ft                |
|                                    | Mean ABS Error         | 5.93                     | 5.28                   | 10 ft                     | 5ft                     |
| Pre-dev Groundwater Heads          | Mean Error             | 1.99                     | 2.24                   | NA                        | NA                      |
|                                    | Mean ABS Error         | 3.59                     | 5.89                   | NA                        | NA                      |
| VHDs                               | Mean ABS Error / Range | 6.78%                    | 6.20%                  | 10%                       | 10%                     |
| HHDs                               | Mean ABS Error / Range | 3.35%                    | 5.28%                  | 10%                       | 10%                     |
| THDs                               | Mean ABS Error / Range | 1.88%                    | 2.07%                  | 20%                       | 20%                     |
| Incremental Baseflows              | Mean ABS Error / Range | 15.29%                   | NA                     | 40%                       | NA                      |

**Table 1 – Calibration Target Metrics.**

| Hydrostratigraphic Unit                                                 | Units  | Calibrated Value | Minimum Bound | Maximum Bound |
|-------------------------------------------------------------------------|--------|------------------|---------------|---------------|
| Horizontal Hydraulic Conductivity                                       |        |                  |               |               |
| Sand and Gravel Aquifer (layer 1)                                       | ft/day | 7.38             | 3.50          | 453           |
| Ratio of Horizontal to Vertical Hydraulic Conductivity                  |        |                  |               |               |
| Sand and Gravel Aquifer (layer 1)                                       | -      | 14.5             | 5.00          | 35.0          |
| Intermediate Aquifer System (layer 2)                                   | -      | 32.0             | 17.5          | 52.5          |
| Upper Floridan Aquifer (layer 3)                                        | -      | 2.04             | 1.00          | 52.5          |
| Bucatunna Clay Confining Unit (layer 4 where present)                   | -      | 36.9             | 17.5          | 52.5          |
| Lower Floridan Aquifer (layer 4 & 5)                                    | -      | 17.9             | 17.5          | 52.5          |
| Specific Yield                                                          |        |                  |               |               |
| Sand and Gravel Aquifer (layer 1)                                       | -      | 0.0252           | 0.0250        | 0.300         |
| Storage Coefficient                                                     |        |                  |               |               |
| Intermediate Aquifer System (layer 2)                                   | -      | 1.57E-4          | 1.0E-5        | 1.00E-3       |
| Upper Floridan Aquifer (layer 3)                                        | -      | 5.06E-4          | 1.0E-5        | 1.00E-3       |
| Bucatunna Clay Confining Unit (layer 4 where present)                   | -      | 1.00E-3          | 1.0E-5        | 1.00E-3       |
| Lower Floridan Aquifer (layer 4 & 5)                                    | -      | 2.56E-4          | 1.0E-5        | 1.00E-3       |
| Riverbed Conductance Multiplier                                         |        |                  |               |               |
| Sand and Gravel Aquifer (layer 1)<br>& Upper Floridan Aquifer (layer 3) | -      | 6.29             | 0.10          | 10.0          |


**Table 2 – Non-pilot point calibration parameters.**


|                |     | Instantaneous Rates (ft <sup>3</sup> /d) |          |          | NET Rates ("IN - OUT", ft <sup>3</sup> /d) |           |           | Differences (ft <sup>3</sup> /d) |              |
|----------------|-----|------------------------------------------|----------|----------|--------------------------------------------|-----------|-----------|----------------------------------|--------------|
|                |     | Predev                                   | 2000     | 2015     | Predev                                     | 2000      | 2015      | Predev to 2000                   | 2000 to 2015 |
| CONSTANT HEADS | In  | 5.84E+06                                 | 6.55E+06 | 6.21E+06 | -3.52E+07                                  | -3.35E+07 | -3.40E+07 | 1.65E+06                         | -5.15E+05    |
|                | Out | 4.10E+07                                 | 4.01E+07 | 4.03E+07 |                                            |           |           |                                  |              |
| DRAINS         | In  | 0.00E+00                                 | 0.00E+00 | 0.00E+00 | -2.50E+08                                  | -2.49E+08 | -2.49E+08 | 9.86E+05                         | -1.49E+05    |
|                | Out | 2.50E+08                                 | 2.49E+08 | 2.49E+08 |                                            |           |           |                                  |              |
| GENERAL HEADS  | In  | 7.44E+06                                 | 7.85E+06 | 7.80E+06 | -1.08E+06                                  | -6.80E+05 | -7.05E+05 | 4.03E+05                         | -2.48E+04    |
|                | Out | 8.52E+06                                 | 8.53E+06 | 8.50E+06 |                                            |           |           |                                  |              |
| RECHARGE       | In  | 9.71E+08                                 | 9.71E+08 | 9.71E+08 | 9.71E+08                                   | 9.71E+08  | 9.71E+08  | 0.00E+00                         | 0.00E+00     |
|                | Out | 0.00E+00                                 | 0.00E+00 | 0.00E+00 |                                            |           |           |                                  |              |
| RIVERS         | In  | 3.25E+07                                 | 3.27E+07 | 3.28E+07 | -6.84E+08                                  | -6.82E+08 | -6.82E+08 | 2.24E+06                         | 3.65E+05     |
|                | Out | 7.17E+08                                 | 7.15E+08 | 7.15E+08 |                                            |           |           |                                  |              |
| WELLS          | In  | 0.00E+00                                 | 4.96E+05 | 4.53E+05 | 0.00E+00                                   | -5.75E+06 | -4.79E+06 | -5.75E+06                        | 9.65E+05     |
|                | Out | 0.00E+00                                 | 6.25E+06 | 5.24E+06 |                                            |           |           |                                  |              |
| STORAGE        | In  | 2.23E+03                                 | 4.95E+05 | 4.98E+04 | 1.90E+03                                   | 4.74E+05  | -1.71E+05 | 4.72E+05                         | -6.45E+05    |
|                | Out | 3.22E+02                                 | 2.08E+04 | 2.21E+05 |                                            |           |           |                                  |              |

**Table 3 – Instantaneous model-wide fluxes, net fluxes, and net flux differences at the end of three modeled stress periods: pre-development (“Predev”), 2000, and 2015.**




## FIGURES







**Figure 2 - Model area, model grid, county boundaries, and major Florida cities/towns.**








**Figure 4 – Cross-section of model layering along column 70.**





**Figure 6 – Groundwater head target locations.**







Figure 7 – Vertical head difference (VHD) target locations.





**Figure 8 – Horizontal head difference (HHD) target locations.**





Figure 9 – Temporal head difference (THD) target locations.



Model Domain
  SEAWAT domain
 ● — Upper Floridan Aquifer APT Target
 ● — Undifferentiated Floridan Aquifer System APT Target
 ● — Lower Floridan Aquifer APT Target

**Figure 10 – Transmissivity targets (in ft<sup>2</sup>/day) based on aquifer performance test (APT) results with HSU designations.**





Figure 11 – Pre-development head target locations in the Upper Floridan Aquifer (model layer 3).





 — Model Grid Cells

**Figure 12 – Pilot point locations used to interpolate layer 4 storativity and hydraulic conductivities in layers 2, 3, and 5.**






Figure 13 – Pilot point locations used to interpolate vertical hydraulic conductivity in layer 4.






Figure 14 – Layer 3 horizontal hydraulic conductivity (Kh).






Figure 15 – Layer 5 horizontal hydraulic conductivity (Kh).






Figure 16 – Layer 3 Transmissivity (T).






Figure 17 – Layer 5 Transmissivity (T).




Figure 18 – Layer 2 vertical hydraulic conductivity (Kv).







Figure 19 – Layer 2 leakance.








Figure 21 – Layer 4 leakance.







Figure 22 – Layer 4 confined storage coefficient (storativity).









Figure 24 – Mean absolute error by target well during the transient simulation period (1942-2015).



**Figure 25 – Observed versus Simulated Post-Development (1942-2015) Groundwater Head Targets.**






Figure 26 – Layer 3 observed and simulated 20-ft head contours for year 2000.




Figure 27 – Layer 3 observed and simulated 20-ft head contours for year 2015.




Figure 28 – Mean absolute error (ft) of vertical head difference targets.






Figure 29 – Observed versus Simulated VHD Targets (1942-2015).






Figure 30 – Mean absolute error (ft) of horizontal head difference targets.




**Figure 31 – Observed versus Simulated HHD Targets (1942-2015).**







**Figure 33 – Observed versus Simulated THD Targets (1942-2015).**



|                     |                                   |                                                                  |                                             |
|---------------------|-----------------------------------|------------------------------------------------------------------|---------------------------------------------|
| <b>Model Domain</b> | <b>Modeled 1942 Head Contours</b> | <b>Pre-development Head Contours (Bush &amp; Johnston, 1988)</b> | <b><u>Pre-dev Head Target Locations</u></b> |
|                     |                                   |                                                                  | <b>— SEAWAT Boundary</b>                    |
|                     |                                   |                                                                  | <b>— Well Measurement</b>                   |

**Figure 34 – Pre-development head contours (Layer 3 simulated heads in 1942) and from Bush & Johnston (1988).**







Figure 35 – Observed versus Simulated Pre-Development Groundwater Head Targets.






Figure 36 – Observed versus Simulated Transmissivity Targets.




**Figure 37 – Leakance into the Upper Floridan Aquifer (layer 3) from the Intermediate Aquifer System (Layer 2) for pre-development.**





**Figure 38 – Leakance into the Upper Floridan Aquifer (layer 3) from the Intermediate Aquifer System (Layer 2) for year 2000.**





**Figure 39 – Leakance into the Upper Floridan Aquifer (layer 3) from the Intermediate Aquifer System (Layer 2) for year 2015.**